



# ESP-250/WS - PA Wall Speaker



PA speaker system,  
in a weatherproof white plastic cabinet with aluminium protective grille.

- 100 V line technique
- Hose-proof
- Switchable to 8 Ohm operation
- 5 power taps, 8 Ohm connection and 100 V power selector switch
- 2-way system
- Stainless steel mounting bracket

## Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 100 W
Power rating (RMS)	: 50/40/30/20/10 W (100 V) 50 W (8 Ohm)
Impedance	: 8 Ohm
Frequency range	: 80-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: -
Speaker size	: -
Sensitivity	: 92 dB/W/m
Max. rated SPL	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: -
Protected against ball rebound	: -
Protection class	: IP65
Admiss. ambient temp.	: -20 °C to +50 °C
Power supply	: -
Dimensions	: 157 x 260 x 170 mm
Width	: 157 mm
Height	: 260 mm
Depth	: 170 mm
Weight	: 2.4 kg



Inputs	: spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -