

ESP-215/WS - PA Wall Speaker



Weatherproof PA speaker system,
in a white plastic cabinet with protective aluminium grille.

- 100 V line technique
- Hose-proof
- Switchable to 8 Ohm operation
- 5 power taps, 8 Ohm connection and 100 V power selector switch
- 2-way system
- Stainless steel mounting bracket

Tekniset tiedot:

| | |
|--------------------------------|---|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 60 W |
| Power rating (RMS) | : 15/10/5/2.5/1.5 W (100 V) 30 W (8 Ohm) |
| Impedance | : 8 Ohm |
| Frequency range | : 100-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : 2-way |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 2 |
| Speaker size | : - |
| Sensitivity | : 87 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : IP65 |
| Admiss. ambient temp. | : -20 °C to +50 °C |
| Power supply | : - |
| Dimensions | : 98 x 195 x 105 mm |
| Width | : 98 mm |
| Height | : 195 mm |
| Depth | : 105 mm |
| Weight | : 0.85 kg |



| | |
|------------------------|------------------------------|
| Inputs | : spring-load. speaker term. |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |