

ESP-90/WS - PA Wall Speaker

100V



PA wall speaker

- 100 V line technique via audio transformer with 3 power taps
- White plastic housing (surface-mount version with open rear panel) with protective metal grille
- Supplied with mounting accessories

Tekniset tiedot:

| | |
|--------------------------------|--------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 6/3/1.5 W |
| Impedance | : - |
| Frequency range | : 80-19,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : - |
| Speaker size | : 130 cm |
| Sensitivity | : - |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : - |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : ~ 168 mm x 72 mm |
| Width | : ~ 168 mm |
| Height | : - |
| Depth | : 72 mm |
| Weight | : 600 g |



| | |
|------------------------|-----|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |