

ESP-63/WS - PA Wall Speaker

100V



PA wall speaker

- 100 V line technique via audio transformer with 2 power taps
- 2-way system with good sound characteristics
- Plastic cabinet of special design with protective metal grille
- Closed rear panel, screwed
- Horizontal and vertical mounting possible

Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 6/3 W
Impedance	: -
Frequency range	: 100-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2
Speaker size	: -
Sensitivity	: 91 dB/W/m
Max. rated SPL	: 101 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: screws
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 240 x 340 x 105 mm
Width	: 240 mm
Height	: 340 mm
Depth	: 105 mm
Weight	: 1.6 kg



Inputs	: power taps
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -