

EDL-412/SW - PA Loudspeaker

100V

8Ω



IP44

new



Weatherproof PA ball speaker

- 100 V line technique or 8 Ohm operation
- Black ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Supplied with 480 cm connection cable and canopy

Tekniset tiedot:

| | |
|--------------------------------|--------------------------|
| Active/passive | : passive |
| Transmission method | : 100 V or low-impedance |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 10/5/2.5 W |
| Impedance | : 8 Ohm |
| Frequency range | : 160-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : - |
| Sensitivity | : 92 dB/W/m |
| Max. rated SPL | : - |
| Beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : ABS, UL 94V-0 |
| Colour | : black |
| Mounting device | : cable with canopy |
| Protected against ball rebound | : - |
| Protection class | : IP44 |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 184 mm |
| Width | : 184 mm |
| Height | : - |
| Depth | : - |



| | |
|--------------------------------|-----------------------|
| Weight | : 1.65 kg |
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.3 x 0.22 x 0.23 m |
| Gross weight | : 2 kg |
| Net weight | : 1.65 kg |