

## IT-350/EN - Horn Speaker



Weatherproof horn speaker (music horn), 2-way technology and EN 54-24 certification

- 100 V line technique with 4 power taps: 30/15/7.5/3.75 W
- Weatherproof and IP66 certified
- High-quality music reproduction
- 16 cm bass-midrange speaker and 25 mm (1") horn
- Robust light grey ABS plastic housing
- Supplied with mounting bracket and stainless steel screws

## Tekniset tiedot:

|                                |                      |
|--------------------------------|----------------------|
| Active/passive                 | : passive            |
| Transmission method            | : 100 V              |
| Total output power             | : -                  |
| Power rating (RMS)             | : -                  |
| Total power rating             | : 30 W               |
| Power rating (RMS)             | : 30/15/7.5/3.75 W   |
| Impedance                      | : -                  |
| Frequency range                | : 100-20,000 Hz      |
| THD                            | : -                  |
| S/N ratio                      | : -                  |
| Input signal                   | : -                  |
| System                         | : -                  |
| Full range speaker             | : -                  |
| Bass speaker                   | : 16 cm (6")         |
| Midrange speaker               | : -                  |
| Tweeter                        | : 25 mm (1")         |
| Number of speakers             | : 2                  |
| Speaker size                   | : 16 cm              |
| Sensitivity                    | : 101 dB/W/m         |
| Max. rated SPL                 | : 116 dB             |
| Radiation angle, horizontal    | : 100°               |
| Radiation angle, vertical      | : 60°                |
| Features                       | : 2-way              |
| Housing material               | : ABS                |
| Colour                         | : light grey         |
| Mounting device                | : mounting bracket   |
| Protected against ball rebound | : -                  |
| Protection class               | : IP66               |
| Admiss. ambient temp.          | : -20 °C to +90 °C   |
| Power supply                   | : -                  |
| Dimensions                     | : 370 x 250 x 330 mm |
| Width                          | : 370 mm             |
| Height                         | : 250 mm             |
| Depth                          | : 330 mm             |
| Weight                         | : 4.5 kg             |



|                        |                       |
|------------------------|-----------------------|
| Inputs                 | : -                   |
| Outputs                | : -                   |
| Replacement voice coil | : -                   |
| Other features         | : weatherproof, EN 54 |
| Accessories            | : -                   |