



SP-8/150PRO - PA Woofer



Compact PA bass speaker, subwoofer, 150 W, 8 Ohm

- 20 cm (8") bass speaker and subwoofer of high power capability
- Heat-resistant voice coil and ventilated drive system
- Extra long excursion for a deep bass reproduction of high volumes
- Progressive cone suspension for a high operating reliability
- Robust diecast aluminium basket
- Ideally suited for 2-way systems and compact subwoofers

HOBBY HiFi 02/2019



“An excellent bass-midrange speaker with an impressive level stability for 2-way and 3-way applications. It features an excellent price-performance ratio.”

Tekniset tiedot:

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: f3-3,000 Hz
Resonant frequency (fs)	: 56 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 150 W
Peak music power output (MAX)	: 300 W
Sensitivity	: 93 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: 0.35 mm/N
Moving mass (Mms)	: 22.8 g
Mech. Q factor (Qms)	: 1.52
Electr. Q factor (Qes)	: 0.41
Total Q factor (Qts)	: 0.32
Equivalent volume (Vas)	: 22 l
DC resistance (Re)	: 7.2 Ohm
Force factor (BxL)	: 11.96 Tm
Voice coil induct. (Le)	: 2.0 mH
Voice coil diameter	: $\tilde{\sim}$ 50 mm
Voice coil former	: aluminium
Linear excursion (X _{MAX})	: \pm 6 mm
Eff. cone area (Sd)	: 213 cm ²
Magnet weight	: 850 g
Magnet diameter	: $\tilde{\sim}$ 120 mm
Mounting cutout	: $\tilde{\sim}$ 185 mm
Mounting depth	: 90 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\tilde{\sim}$ 210 mm x 100 mm
Outside diameter	: $\tilde{\sim}$ 210 mm
Width	: $\tilde{\sim}$ 210 mm



Height	: -
Depth	: 100 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 2.52 kg
Packing unit	: 1
Type of speaker	: 8"