

ESP-62AB/WS - PA Wall Speaker



PA A/B wall speaker,
with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 13 cm full range speaker with dual voice coil
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Symmetrical design allows for horizontal and vertical mounting
- Plastic cabinet with open rear panel and protective metal front grille
- Supplied with screws and wall plugs

Tekniset tiedot:

| | |
|--------------------------------|--------------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 2 x 6/3/1.5 W |
| Impedance | : - |
| Frequency range | : 80-19,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : 13 cm, dual voice coil |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : 13 cm |
| Sensitivity | : 93 dB/W/m |
| Max. rated SPL | : 101 dB |
| Radiation angle, horizontal | : 160° |
| Radiation angle, vertical | : 160° |
| Features | : - |
| Housing material | : ABS |
| Colour | : white, RAL 9010 |
| Mounting device | : screws |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : -10 °C to +50 °C |
| Power supply | : - |
| Dimensions | : 240 x 330 x 83 mm |
| Width | : 240 mm |
| Height | : 330 mm |
| Depth | : 83 mm |
| Weight | : 1.5 kg |



| | |
|------------------------|-----|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |