

## MPX-4PA - Stereo Mixer



### 3-zone mixer

- 3 zones with user-defined routing of all input channels
- XLR and RCA zone outputs
- 6 input channels (4 stereo ways, 2 microphone ways)
- Both microphone ways can only be routed together
- Recessed gain control for each input channel
- Microphone ways, each with 2-way tone control, talkover and PAD switch
- Stereo channels, switchable 2 x phono/line and 2 x line/line
- Zone outputs, each with 3-way equalizer, LED level display of the stereo master, balance control, pre-fader listening (PFL) and mono/stereo selector switch
- Adjustable headphone output with pre-fader listening (PFL) to the stereo input channels and zone outputs
- Connection for gooseneck light GNL-204

## Tekniset tiedot:

No. of channels	: 6
No. of inputs	: 12
Mic input	: 1.5 mV, 2 x 6.3 mm jack
Line input	: 150 mV, 5 x RCA L/R
CD input	: 150 mV, 1 x RCA L/R
Phono input	: 3 mV, 2 x RCA L/R
Tape (play)	: -
Aux input	: -
Insert input	: -
Effect return	: -
Master output	: 1 V/600 Ohm, 3 x 3-pole XLR L/R, 3 x RCA L/R
Record output	: -
Monitor output	: -
Booth output	: -
Aux output	: -
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: 8 Ohm, 1 x 6.3 mm jack
Gooseneck lamp	: 12 V/0.75 W, 1 x BNC
WiFi	: -
USB	: -
<b>Bluetooth</b>	: -
Frequency range	: 20-20,000 Hz
THD	: 0.1%
S/N ratio	: 61 dB, unweighted
Crosstalk	: -
Equalizer bass	: +12 dB, -12 dB/50 Hz
Equalizer midrange	: +12 dB, -12 dB/1 kHz
Equalizer treble	: +12 dB, -12 dB/10 kHz
equalizer	: -
Talkover	: -16 dB
Phantom power	: -
Crossfader	: -

Media player	: -
Amplifier	: -
Power supply	: &acd; 230Â V/50Â Hz/20Â VA
Mains voltage	: &sim; 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 20 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 177 mm
Depth	: 105 mm
Rack spaces, RS	: 4
Weight	: 4 kg