

MPX-622/SW - Stereo Mixer



6-channel stereo audio mixer,
particularly suitable for PA and DJ applications.

- 2 mono microphone channels with talkover switch and 2-way tone control
- 4 stereo input channels, switchable phono/line (channels 1 and 2) or line/line (channels 3 and 4)
- 1 stereo master output
- 1 stereo record output, independent of the master
- 3-way equalizer with centre click for master output and record output
- Pre-fader listening to each stereo input channel and the master output via adjustable stereo headphone output
- Switchable crossfader for crossfading between channels 1-4, any assignment possible
- Stereo LED level display

Tekniset tiedot:

| | |
|--------------------|--------------------------------|
| No. of channels | : 6 |
| No. of inputs | : 8 |
| Mic input | : 1 mV, 2 x 6.3 mm jack |
| Line input | : 150 mV, 5 x RCA L/R |
| CD input | : 150 mV, 1 x RCA L/R |
| Phono input | : 3 mV, 2 x RCA L/R |
| Tape (play) | : - |
| Aux input | : - |
| Insert input | : - |
| Effect return | : - |
| Master output | : 0.775 V/600 Ohm, 1 x RCA L/R |
| Record output | : 0.775 V/600 Ohm, 1 x RCA L/R |
| Monitor output | : - |
| Booth output | : - |
| Aux output | : - |
| Insert output | : - |
| Effect send | : - |
| Control room | : - |
| Tape (rec) | : - |
| Headphones | : ? 8 Ohm, 1 x 6.3 mm jack |
| Gooseneck lamp | : - |
| WiFi | : - |
| USB | : - |
| Bluetooth | : - |
| Frequency range | : 20-20,000 Hz |
| THD | : 0.1% |
| S/N ratio | : 65 dB |
| Crosstalk | : - |
| Equalizer bass | : ± 10 dB/100 Hz |
| Equalizer midrange | : ± 10 dB/1 kHz |
| Equalizer treble | : ± 10 dB/10 kHz |
| equalizer | : - |
| Talkover | : -15 dB |
| Phantom power | : - |
| Crossfader | : yes |

| | |
|--|------------------------------|
| Media player | : - |
| Amplifier | : - |
| Power supply | : ∿ 230Â V/50Â Hz/10Â VA |
| Mains voltage | : ∼ 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 10 VA |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 482 mm |
| Height | : 89 mm |
| Depth | : 95 mm |
| Rack spaces, RS | : 2 |
| Weight | : 2.4 kg |