

## ULM-164/SW - Line Mixer



Universal line mixer,  
6 channels.

- 6 stereo inputs/mono inputs
- 2 stereo outputs, independent of each other (master 1 via RCA and 6.3 mm jack), 1 mono output
- 3-way equalizer
- LED VU meter, switchable for both outputs
- Clip LED for each channel
- Balance controls with centre click for the stereo input channels
- Extended muting function
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RS

## Tekniset tiedot:

|                    |   |
|--------------------|---|
| No. of channels    | : 6   |
| No. of inputs      | : 12  |
| Mic input          | : -   |
| Line input         | : 150 mV/50 kOhm (stereo), 6 x RCA L/R 150 mV/25 kOhm (mono), 6 x 6.3 mm jack, unbal. |
| CD input           | : -   |
| Phono input        | : -   |
| Tape (play)        | : -   |
| Aux input          | : -   |
| Insert input       | : -   |
| Effect return      | : -   |
| Master output      | : 1 V/600 Ohm (stereo), 2 x RCA (1 x 6.3 mm) L/R 2 V/600 Ohm (mono), 1 x 6.3 mm jack  |
| Record output      | : -   |
| Monitor output     | : -   |
| Booth output       | : -   |
| Aux output         | : -   |
| Insert output      | : -   |
| Effect send        | : -   |
| Control room       | : -   |
| Tape (rec)         | : -   |
| Headphones         | : ? 8 Ohm, 1 x 6.3 mm jack  |
| Gooseneck lamp     | : -   |
| WiFi               | : -   |
| USB                | : -   |
| <b>Bluetooth</b>   | : -   |
| Frequency range    | : 20-20,000 Hz  |
| THD                | : 0.05%   |
| S/N ratio          | : 69 dB, unweighted   |
| Crosstalk          | : -   |
| Equalizer bass     | : $\pm 12$ dB/80 Hz   |
| Equalizer midrange | : $\pm 12$ dB/1 kHz   |
| Equalizer treble   | : $\pm 12$ dB/10 kHz  |
| equalizer          | : -   |
| Talkover           | : -   |
| Phantom power      | : -   |
| Crossfader         | : -   |

|  |                              |
|--|------------------------------|
| Media player                             | : -                          |
| Amplifier                                | : -                          |
| Power supply                             | : &acd; 230Â V/50Â Hz/10Â VA |
| Mains voltage                            | : &sim; 230 V                |
| Mains frequency                          | : 50 Hz                      |
| Power consumption, operation             | : 10 VA                      |
| Operating voltage (possible alternative) | : -                          |
| Power supply (possible alternative)      | : -                          |
| Admiss. ambient temp.                    | : 0-40 °C                    |
| Width                                    | : 482 mm                     |
| Height                                   | : 48 mm                      |
| Depth                                    | : 175 mm                     |
| Rack spaces, RS                          | : 1                          |
| Weight                                   | : 2.3 kg                     |