

SPR-6 - Phono Pre-Amplifier



Stereo phono anti-distortion preamplifier acc. to RIAA, for connecting a turntable to the aux input or line input of a hi-fi system, a mixer or an amplifier, etc. Low hum effect due to metal case and supplied plug-in power supply.

Tekniset tiedot:

| | |
|-----------------------|----------------------------------|
| Description | : anti-distortion preamplifier |
| Frequency range | : 20-20,000 Hz |
| Control range | : - |
| Control frequencies | : - |
| Input signal | : 5 mV/47 kOhm |
| Input sensitivity | : - |
| Input impedance | : - |
| Output signal | : 450 mV/100 kOhm |
| Output impedance | : - |
| Gain | : - |
| Phantom power | : - |
| Compression | : - |
| Gate ratio | : - |
| Crossover frequency | : - |
| High-pass filter | : - |
| Low cut | : - |
| Transmission ratio | : - |
| S/N ratio | : ? 50 dB |
| Channel separation | : - |
| THD | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : via encl. plug-in power supply |
| Dimensions | : 67 x 37 x 121 mm |
| Weight | : 200 g |
| Inputs | : 1 x RCA L/R |
| Outputs | : 1 x RCA L/R |
| Other features | : - |