

ECM-501L/SK - Electret Microphone



Electret tie clip microphone

- Unobtrusive fit due to beige miniature design
- High-quality microphone cartridge with omnidirectional polar pattern
- Removable clip and 1.2 m connection cable
- 3-pole mini XLR inline jack for connection to an optional phantom power supply adapter (EMA-1, EMA-300P) or a pocket transmitter TXS-...HSE

Tekniset tiedot:

| | |
|-------------------------|-----------------------|
| Description | : tie clip microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : omnidir. |
| System | : electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 20-20,000 Hz |
| Nominal impedance | : 1 kOhm |
| Sensitivity | : 5.6 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : 110 dB |
| Power supply | : DC 1.5-9 V |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : Å~ 5 mm x 10 mm |
| Weight | : 5 g |
| Cable | : 1.2 m |
| Connection | : 3-pole mini XLR |