

## PPA-100/SW - Headphones Amplifier



Stereo headphone amplifier

- 6 separate headphone amplifiers, each with 1 level control and 1 signal/clip LED as well as main/solo switching
- 1 input (solo) per amplifier, switchable to common main input (main)
- Main input with low/high selector switch for matching the input signal
- Inputs: solo (stereo) 6 x 6.3 mm jack, main (stereo) 2 x 6.3 mm jack, 2 x RCA L/R
- Outputs: headphones (stereo) 6 x 6.3 mm jack

## Tekniset tiedot:

Description	: headphone amplifier
Frequency range	: 5-30,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: 250 mV/50 kOhm (solo)250 mV/50 kOhm (main low)2.2 V/60 kOhm (main high)
Input sensitivity	: -
Input impedance	: -
Output signal	: 2 x 16 mW/8 Ohm2 x 45 mW/32 Ohm2 x 75 mW/600 Ohm
Output impedance	: -
Gain	: -
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: -
S/N ratio	: ? 60 dB
Channel separation	: 50 dB
THD	: 0.02%
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230 V/50 Hz/11 VA
Dimensions	: 482 x 44 x 185 mm, 1 RS
Weight	: 2.3 kg
Inputs	: 2 x RCA L/R (main), 2 x 6.3 mm jack (main), 6 x 6.3 mm jack (solo)
Outputs	: 6 x 6.3 mm jack (headphones)
Other features	: -