

HPR-6 - Headphones Amplifier



Efficient stereo headphone amplifier,
can also be used as a small power amplifier for 4-8 Ohm speaker systems

- Robust metal housing
- Stereo RCA input
- 6.3 mm stereo output
- Volume control and balance control

Tekniset tiedot:

| | |
|-----------------------|--|
| Description | : stereo headphone amplifier |
| Frequency range | : 19-40,000 Hz |
| Control range | : - |
| Control frequencies | : - |
| Input signal | : 110 mV-4 V |
| Input sensitivity | : - |
| Input impedance | : - |
| Output signal | : 2 x 525 mW/2 x 1,500 mW/4 Ohm, 2 x 330 mW/2 x 750 mW/8 Ohm, 2 x 114 mW/2 x 200 mW/32 Ohm |
| Output impedance | : - |
| Gain | : - |
| Phantom power | : - |
| Compression | : - |
| Gate ratio | : - |
| Crossover frequency | : - |
| High-pass filter | : - |
| Low cut | : - |
| Transmission ratio | : - |
| S/N ratio | : 69 dB |
| Channel separation | : - |
| THD | : 1% |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : via encl. plug-in power supply |
| Dimensions | : 120 x 68 x 36 mm |
| Weight | : 288 g |
| Inputs | : 2 x RCA L/R |
| Outputs | : 1 x 6.3 mm jack |
| Other features | : - |