

RL-1EN - Wall Speaker



PA sound projector for wall mounting,
with EN 54-24 certification.

- 100 V line technique
- 13 cm full range speaker
- 100 V transformer with power taps on the cable 6/3/1.5 W
- Connection via 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

Tekniset tiedot:

| | |
|--------------------------------|-------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 6/3/1.5 W |
| Impedance | : - |
| Frequency range | : 80-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : 13 cm |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : - |
| Speaker size | : 13 cm |
| Sensitivity | : 93 dB/W/m |
| Max. rated SPL | : 101 dB |
| Radiation angle, horizontal | : 130° |
| Radiation angle, vertical | : 130° |
| Features | : - |
| Housing material | : aluminium |
| Colour | : white |
| Mounting device | : bracket |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 144 mm x 210 mm |
| Width | : 144 mm |
| Height | : - |
| Depth | : 210 mm |
| Weight | : 1.9 kg |



| | |
|------------------------|-----|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |