

## IT-15EN - Horn Speaker



Weatherproof horn speakers,  
with EN 54-24 certification.

- 100 V line technique
- IP66 tested
- Light grey ABS housing (self-extinguishing, complies with the standard UL 94V-0)
- Cable inlet via high-strength cable gland
- Suitable for general indoor and outdoor applications
- Integrated high-pass filter for optimising the sound and stability
- Supplied with mounting bracket

## Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 15 W
Power rating (RMS)	: 15/7.5/3.75 W
Impedance	: -
Frequency range	: 350-10,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: -
Sensitivity	: 110 dB/W/m
<b>Max. rated SPL</b>	: -
Radiation angle, horizontal	: 110°
Radiation angle, vertical	: 55°
Features	: EN 54-24 certification
Housing material	: ABS, UL 94V-0
Colour	: light grey
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: IP66
Admiss. ambient temp.	: -25 °C to +70 °C
<b>Power supply</b>	: -
Dimensions	: 180 x 120 x 230 mm
Width	: 180 mm
Height	: 120 mm
Depth	: 230 mm
Weight	: 2.1 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: weatherproof
Accessories	: -