

# AKB-160 - Amplifier Module

100V



PA amplifier module,  
with 100 V output.

- 1 x 40 W
- Silent operation due to fanless cooling concept
- Balanced line input (XLR) and unbalanced line input (RCA)
- Speaker output via spring-loaded speaker terminals
- Volume control
- Metal housing with mounting brackets

## Tekniset tiedot:

Peak output power	: 60 W
Power rating	: 40 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: 40 W
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 1
Zones	: -
Inputs	: 390 mV/26 kOhm, bal.420Â mV/11Â kOhm, unbal.
Attenuation factor	: -
Frequency range	: 17-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 80 dB
Crosstalk attenuation	: -
THD	: < 1%
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 75 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 213 mm
Height	: 55 mm

Depth

: 238 mm





---

Rack spaces, RS	: -
Weight	: 3.2 kg
Connections	: 1 x XLR (line)1 x RCA L/R (line)