

ESP-62/WS - PA Wall Speaker



PA wall speaker, with EN 54-24 certification.

- 100 V line technique via audio transformer with 3 power taps
- Full range speaker with a high-quality sound and a clear voice reproduction
- Plastic cabinet of a special design (open rear panel) with protective metal grille
- Symmetrical design allows for horizontal and vertical mounting
- Supplied with mounting screws and screw head covers
- Ball-proof according to DIN 18032, Part 3

Tekniset tiedot:

| | |
|--------------------------------|---------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 6/3/1.5 W |
| Impedance | : - |
| Frequency range | : 100-19,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : - |
| Speaker size | : 130 mm |
| Sensitivity | : 93 dB/W/m |
| Max. rated SPL | : 101 dB |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : - |
| Protected against ball rebound | : yes |
| Protection class | : - |
| Admiss. ambient temp. | : -10 °C to +50 °C |
| Power supply | : - |
| Dimensions | : 240 x 330 x 85 mm |
| Width | : 240 mm |
| Height | : 330 mm |
| Depth | : 85 mm |
| Weight | : 1.2 kg |



| | |
|------------------------|-----|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |