

## PA-24ESP - Emergency Power Supply



24 V emergency power supply,  
for our PA components with 24 V connection.

- Possible to install 2 x rechargeable lead battery NPA-12/24
- Screw terminal for external 24 V rechargeable batteries
- Maximum charging current: 2.5 A
- Electronic charging control with overload protection, protection against total discharge and trickle charge
- 1 x output DC 24 V/1 A (unswitched)
- 2 x output DC 24 V/32 A
- 3 x output DC 24 V/16 A
- Power supply: &acd; 230 V/50 Hz/110 VA
- Dimensions: 482 x 135 x 405 mm
- Weight: 11.7 kg

## Tekniset tiedot:

|                       |                                |
|-----------------------|--------------------------------|
| Description           | : emergency power supply       |
| Nominal value         | : DC 24 V                      |
| Type                  | : -                            |
| Colour                | : -                            |
| Material              | : -                            |
| Suitable for          | : PA, 24 V                     |
| Power supply          | : &acd;Â 230Â V/50Â Hz/110Â VA |
| Admiss. ambient temp. | : 0-40 °C                      |
| Dimensions            | : 482 x 135 x 405Â mm          |
| Length                | : -                            |
| Mounting dimensions   | : -                            |
| Weight                | : 11.52 kg                     |
| Connections           | : screw terminals              |
| Other features        | : -                            |
| Packing unit          | : 1                            |