



DT-19SU - HiFi Dome Tweeter



DT-19SU



Hi-fi dome tweeter, 50 W, 8 Ohm

- 19 mm soft dome, laminate technology
- Double magnet
- Robust plastic front
- Low cone weight
- Optimum brilliance
- For hi-fi applications of high requirements, especially in 3-way systems

Tekniset tiedot:

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: fx-20,000 Hz
Resonant frequency (fs)	: 1,500 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: 3,000 Hz
Power rating (RMS)	: 50 W
Peak music power output (MAX)	: 80 W
Sensitivity	: 91 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: $\tilde{\sim}$ 19 mm
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: $\tilde{\sim}$ 55 mm
Mounting cutout	: $\tilde{\sim}$ 66 mm
Mounting depth	: 33 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\tilde{\sim}$ 100 x 33 mm
Outside diameter	: $\tilde{\sim}$ 100 mm
Width	: $\tilde{\sim}$ 100 mm

Height	: -
Depth	: 33 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.397 kg
Packing unit	: 1
Type of speaker	: -