

Tekniset tiedot:

| | |
|---|-----------------------------------|
| Impedance (Z) | : 8 Ohm |
| Transmission method | : - |
| Frequency range | : fx-5,000 Hz |
| Resonant frequency (fs) | : 80 Hz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : - |
| Power rating (RMS) | : 40 W |
| Peak music power output (MAX) | : 80 W |
| Sensitivity | : 87 dB/W/m |
| Max. rated SPL | : - |
| Max. voltage | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Suspension compl. (Cms) | : 0.79 mm/N |
| Moving mass (Mms) | : 4.9 g |
| Mech. Q factor (Qms) | : 3.05 |
| Electr. Q factor (Qes) | : 0.67 |
| Total Q factor (Qts) | : 0.55 |
| Equivalent volume (Vas) | : 3.2 l |
| DC resistance (Re) | : 6.2 Ohm |
| Force factor (BxL) | : 4.81 Tm |
| Voice coil induct. (Le) | : 0.3 mH |
| Voice coil diameter | : $\tilde{\sim}$ 25 mm |
| Voice coil former | : aluminium |
| Linear excursion (X _{MAX}) | : \pm 1.5 mm |
| Eff. cone area (Sd) | : 55 cm ² |
| Magnet weight | : 250 g |
| Magnet diameter | : $\tilde{\sim}$ 72 mm |
| Mounting cutout | : $\tilde{\sim}$ 90 mm |
| Mounting depth | : 51.2 mm |
| Mounting hole diameter | : $\tilde{\sim}$ 82 mm |
| Hole spacing X-axis | : - |
| Hole spacing Y-axis | : - |
| Dimensions | : $\tilde{\sim}$ 124.3 mm x 55 mm |
| Outside diameter | : $\tilde{\sim}$ 124.3 mm |
| Width | : $\tilde{\sim}$ 124.3 mm |



| | |
|-----------------------|-----------|
| Height | : - |
| Depth | : 55 mm |
| Protective class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Weight | : 0.63 kg |
| Packing unit | : 1 |
| Type of speaker | : 4" |