

SA-100 - Amplifier

2x50
W MAX



Compact universal stereo amplifier, 50 W

- Silent operation due to fanless cooling concept
- Additional 3.5 mm connection with switchable sensitivity on the front panel
- USB port on the front panel for power supply and for charging external devices
- Audio source selector switch
- Controls for volume, bass and treble
- 6.3 mm headphone output
- Robust metal housing

Tekniset tiedot:

| | |
|--|--|
| Peak output power | : 2 x 50 W |
| Power rating | : 50 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : 2 x 25 W |
| Power rating at 8 Ohm | : 2 x 20 W |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm | : - |
| bridged operation | |
| Power rating with 8 Ohm | : - |
| bridged operation | |
| Output impedance | : - |
| Channels | : 2 |
| Zones | : - |
| Inputs | : 140 mV/46 kOhm (PC, CD, aux)140 mV/12 kOhm, 25 mV/32 kOhm (player) |
| Attenuation factor | : - |
| Frequency range | : 20-20,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : ± 12 dB |
| Equalizer midrange | : - |
| Equalizer treble | : ± 12 dB |
| S/N ratio | : ? 70 dB |
| Crosstalk attenuation | : - |
| THD | : - |
| Mains voltage | : \sim 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 150 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 212 mm |
| Height | : 56 mm |

Depth

: 250 mm



| | |
|-----------------|--|
| Rack spaces, RS | : - |
| Weight | : 2.6 kg |
| Connections | : 1 x RCA L/R (PC), 1 x RCA L/R (CD), 1 x RCA L/R (aux), 1 x 3.5 mm jack (player), 4 x spring-load. speaker term. (speakers) |