

# MC-52USB/WS - Main Distributor incl. USB



Tabletop multi-socket power strip

- Elegant design
- 5 earthed sockets turned by 90°, ideally suited for right-angle plugs
- Wide spaced sockets allow operation of power supplies
- Illuminated safety switch, 2 poles, can be switched on/off
- Screw holes for easily mounting the multi-socket power strip in fixed installations, e.g. to the wall
- Child safety sockets
- 2 USB Type-A charging ports
- Output current: 2,100 mA max. (total output current for both USB outputs)
- Cable specifications: H05VV-F3G x 1.5mm<sup>2</sup>
- 1.5 m connection cable with earthed plug

## Tekniset tiedot:

|                        |                                                                        |
|------------------------|------------------------------------------------------------------------|
| Intended use           | : multi-socket power strip                                             |
| Connectors             | : 5 x earthed socket, 90°,<br>2 x USB Type-A jack,<br>1 x earthed plug |
| Cable specification    | : H05VV-F3G x 1.5mm <sup>2</sup>                                       |
| Length                 | : 1.4 m                                                                |
| Colour                 | : white                                                                |
| Cable diameter         | : -                                                                    |
| Metre marking          | : -                                                                    |
| Minimum bending radius | : -                                                                    |
| Shielding              | : -                                                                    |
| Shielding value        | : -                                                                    |
| Impedance              | : -                                                                    |
| Attenuation            | : -                                                                    |
| Capacitance            | : -                                                                    |
| Power rating           | : 3,500 W                                                              |
| Rated current          | : -                                                                    |
| Internal conductor     | : 3 x 1.5 mm <sup>2</sup>                                              |
| No. of cores           | : 3                                                                    |
| Material               | : -                                                                    |
| Packaging              | : -                                                                    |
| Weight                 | : 644 g                                                                |
| Position               | : -                                                                    |
| Special feature        | : with switch                                                          |
| Other features         | : -                                                                    |