

CC-145 - Compact Connecting Terminal



Connecting terminal from WAGO

- 5-conductor terminal with operating levers
- Individually combinable wires and cross sections from 0.14 to 4 mm²
- Power rating: 450 V/32 A
- Continuous operating temperature: up to 85 °C
- Correct position of the conductor and stripping length can be visually checked due to transparent housing
- Two test slots for any standard test prod
- Of very compact size, thus, ideally suited for the application in confined spaces

Tekniset tiedot:

| | |
|------------------------------|---|
| Description | : connecting terminal |
| Type | : WAGO |
| Quantity | : 1 |
| Features | : operating levers |
| Colour/colour coding | : transparent |
| Power rating | : 450 V/32 A |
| Insulating resistance | : - |
| Dielectric strength | : 4 kV |
| Certification | : UL, ABS, LR |
| Pole number | : 5 |
| Cable inlet | : AWG 24-12 |
| Suitable cable cross section | : flexible conductors: 0.14-4 mm ² rigid conductors: up to 0.2-4 mm ² |
| Connection | : 5-conductor terminal with operating levers |
| Strain relief | : - |
| Cable bending protection | : - |
| Stereo | : - |
| Mono | : - |
| Switches | : - |
| Material | : - |
| Central fixing | : - |
| Contact type | : - |
| No. of contacts | : - |
| Contact width | : - |
| Contact distance | : - |
| Admiss. ambient temp. | : 85 °C |
| Dimensions | : 29.9 x 8.3 x 18.6 mm |
| Diameter | : - |
| Length | : - |
| Weight | : 4 g |
| Other features | : - |