

## ATS-12HT - Handheld Transmitter



Hand-held microphone with integrated transmitter

- Matching the 16-channel mono PLL audio transmission system of the ATS-10 series and ATS-16R
- Electret microphone cartridge, cardioid polar pattern
- 16 selectable channels
- Pilot tone
- Mute function
- Push-to-talk function
- Adjustable transmitting power (high: (tm) 10mW/low: (tm) 1 mW)
- Operating range: approx. 50 m
- LCD for indicating channel and battery status
- Power supply via 2 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: Ø 35 mm x 200 mm
- Weight: 93 g

Licence-free in the EU.

## Tekniset tiedot:

Description	: hand-held microphone transmitter
Version	: -
Transmission method	: wireless
Polar pattern	: cardioid
System	: electret
Carrier frequency range	: 863-865 MHz
Transmitting power	: ?10 mW/?1 mW
Power supply	: 2 x 1.2 V NiMH rech. batt. AA size
Operating time	: 12 h/15 h
Audio frequency range	: -
Nominal impedance	: -
Sensitivity	: -
S/N ratio	: -
Max. sound pressure	: -
Power supply	: -
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: Å~ 35 mm x 200 mm
Weight	: 93 g
Cable	: -
Connection	: -