

## ATS-22T - 16 Channel Mini. Transmitter



16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

16-channel miniature transmitter,  
for microphone operation and audio line signals, with intercom function.

- Supplied with headset
- Activation switch for intercom function with the receiver ATS-22R
- Audio line input via 3.5 mm jack at the headset
- LCD for indicating channel and battery status
- Mute button
- Transmitting power: (tm) 10 mW (EIRP), operating range: approx. 70 m
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

Licence-free in the EU.

## Tekniset tiedot:

### General information

|                            |   |
|----------------------------|---|
| Description                | : -   |
| Carrier frequency range    | : 16-channel digital miniature transmitter                  |
| Audio frequency range      | : 863-865 MHz   |
| Channels                   | : -   |
| THD                        | : -   |
| Dynamic range              | : -   |
| RF S/N ratio               | : -   |
| Operating time             | : -   |
| Admiss. ambient temp.      | : 0-40 °C   |
| Power supply               | : -   |
| Dimensions                 | : -   |
| Total weight               | : -   |
| Connections                | : -   |
| Specifications transmitter | :   |
| Transmitting power         | : ? 10 mW   |
| Operating range            | : 70 m  |
| Power supply transmitter   | : integrated rech. lithium batt. (3.7 V/600 mAh)            |
| Width transmitter          | : 40 mm   |
| Height transmitter         | : 80 mm   |
| Depth transmitter          | : 12 mm   |
| Weight transmitter         | : 37 g  |
| Connections transmitter    | : 3.5 mm jack (microphone/line in), micro USB charging port |
| Specifications receiver    | : -   |
| Audio signal receiver      | : -   |
| Power supply receiver      | : -   |
| Width receiver             | : -   |
| Height receiver            | : -   |
| Depth receiver             | : -   |
| Weight receiver            | : -   |
| Connections receiver       | : -   |