

PPA-4 - Headphones Amplifier



Stereo headphone amplifier

- 4 separate headphone amplifiers in one housing
- 1 level control each per amplifier
- 6.3 mm stereo input
- 6.3 mm stereo outputs

Tekniset tiedot:

| | |
|-----------------------|---|
| Description | : headphone amplifier |
| Frequency range | : 20-20,000 Hz |
| Control range | : - |
| Control frequencies | : - |
| Input signal | : 300 mV |
| Input sensitivity | : - |
| Input impedance | : - |
| Output signal | : 2Â xÂ 16Â mW/8Â Ohm, 2Â xÂ 35Â mW/32Â Ohm, 2Â xÂ 15Â mW/600Â Ohm (per headphone) |
| Output impedance | : - |
| Gain | : - |
| Phantom power | : - |
| Compression | : - |
| Gate ratio | : - |
| Crossover frequency | : - |
| High-pass filter | : - |
| Low cut | : - |
| Transmission ratio | : - |
| S/N ratio | : 64 dB |
| Channel separation | : - |
| THD | : 0.1% |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : via encl. plug-in power supply |
| Dimensions | : 117 x 93 x 40Â mm |
| Weight | : 560 g |
| Inputs | : 1 x 6.3Â mm jack |
| Outputs | : 4 x 6.3Â mm jack |
| Other features | : - |