

PPA-100/SW - Headphones Amplifier



Stereo headphone amplifier

- 6 separate headphone amplifiers, each with 1 level control and 1 signal/clip LED as well as main/solo switching
- 1 input (solo) per amplifier, switchable to common main input (main)
- Main input with low/high selector switch for matching the input signal
- Inputs: solo (stereo) 6 x 6.3 mm jack, main (stereo) 2 x 6.3 mm jack, 2 x RCA L/R
- Outputs: headphones (stereo) 6 x 6.3 mm jack

Tekniset tiedot:

| | |
|-----------------------|---|
| Description | : headphone amplifier |
| Frequency range | : 5-30,000 Hz |
| Control range | : - |
| Control frequencies | : - |
| Input signal | : 250 mV/50 kOhm (solo)250 mV/50 kOhm (main low)2.2 V/60 kOhm (main high) |
| Input sensitivity | : - |
| Input impedance | : - |
| Output signal | : 2 x 16 mW/8 Ohm2 x 45 mW/32 Ohm2 x 75 mW/600 Ohm |
| Output impedance | : - |
| Gain | : - |
| Phantom power | : - |
| Compression | : - |
| Gate ratio | : - |
| Crossover frequency | : - |
| High-pass filter | : - |
| Low cut | : - |
| Transmission ratio | : - |
| S/N ratio | : ? 60 dB |
| Channel separation | : 50 dB |
| THD | : 0.02% |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : ∿ 230 V/50 Hz/11 VA |
| Dimensions | : 482 x 44 x 185 mm, 1 RS |
| Weight | : 2.3 kg |
| Inputs | : 2 x RCA L/R (main), 2 x 6.3 mm jack (main), 6 x 6.3 mm jack (solo) |
| Outputs | : 6 x 6.3 mm jack (headphones) |
| Other features | : - |