

## HSE-150A/SK - Headworn Microphone



Beige-coloured, all-purpose headband microphone for adapter systems. This microphone is comfortable to wear, provides an absolutely secure fit and the high-quality back electret cartridge ensures an excellent audio reproduction of presentations and vocals. Thanks to the omnidirectional polar pattern, even a less than perfectly aligned cartridge is no problem. The flexible connection cable features a plug with latching device to ensure a safe connection with the corresponding adapter. Additional connection adapters for devices from other manufacturers are available at option.

Ultra-light headband microphone

- Omnidirectional polar pattern
- High-quality back electret cartridge
- Plug with latching device
- Supplied with adapters for the TXS-...HSE series (3-pole mini XLR) and pocket transmitters from JTS (4-pole mini XLR)
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Removable sweat-proof connection cable with 2.5 mm stereo plug (replacement connection cable: HSE-70C)
- Optional adapters allow application with devices from other manufacturers
- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

## Tekniset tiedot:

|                         |  |
|-------------------------|--|
| Description             | : headband microphone                      |
| Version                 | : -  |
| Transmission method     | : cable                                    |
| Polar pattern           | : omnidir.                                 |
| System                  | : back electret                            |
| Carrier frequency range | : -  |
| Transmitting power      | : -  |
| Power supply            | : -  |
| Operating time          | : -  |
| Audio frequency range   | : 20-20,000 Hz                             |
| Nominal impedance       | : 1 kOhm                                   |
| Sensitivity             | : 8 mV/Pa                                  |
| S/N ratio               | : -  |
| Max. sound pressure     | : 130 dB                                   |
| Power supply            | : DC 1.5-9 V                               |
| Gooseneck length        | : -  |
| Housing material        | : -  |
| Admiss. ambient temp.   | : 0-40 °C                                  |
| Dimensions              | : -  |
| Weight                  | : 7 g                                      |
| Cable                   | : -  |
| Connection              | : 2.5 mm stereo plug 2 connection adapters |