

TXS-606 - Receiver



Multifrequency receiver unit,
with UHF PLL technology.

- 1,000 selectable UHF frequencies (672.000-696.975 MHz) in 10 groups with 100 frequencies each
- ACT function for transmitting selected frequency to pocket transmitter TXS-606LT or hand-held microphone TXS-606HT via infrared signal
- Auto-scan
- True diversity system with removable antennas (BNC connection)
- Volume and squelch controls
- LCD for indicating group/channel, antenna A/B, RF receiving level and AF audio level
- Additional LED level display for indicating audio level
- XLR output and 6.3 mm output
- 8 V supply voltage for active antennas or antenna amplifier (e.g. TXS-875B) is available
- Robust metal housing
- Supplied with power supply

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

Tekniset tiedot:

General information

	: -
Description	: receiver unit
Carrier frequency range	: 672.000-696.975 MHz
Audio frequency range	: 30-18,000 Hz
Channels	: 1
THD	: < 0.5%
Dynamic range	: 100 dB
RF S/N ratio	: 105 dB
Operating time	: -
Admiss. ambient temp.	: 0-40 °C

Power supply : -

Dimensions : -

Total weight : -

Connections : -

Specifications transmitter : -

Transmitting power : -

Operating range : -

Power supply transmitter : -

Width transmitter : -

Height transmitter : -

Depth transmitter : -

Weight transmitter : -

Connections transmitter : -

Specifications receiver : -

Audio signal receiver : 350 mV/600 Ohm (jack) 25 mV/600 Ohm (XLR, bal.)

Power supply receiver : via encl. plug-in power supply

Width receiver : 212 mm

Height receiver : 45 mm

Depth receiver : 180 mm

Weight receiver : 930 g

Connections receiver : 1 x XLR, bal.,
1 x 6.3 mm jack, unbal.