

## TXS-606 - Receiver



Multifrequency receiver unit,  
with UHF PLL technology.

- 1,000 selectable UHF frequencies (672.000-696.975 MHz) in 10 groups with 100 frequencies each
- ACT function for transmitting selected frequency to pocket transmitter TXS-606LT or hand-held microphone TXS-606HT via infrared signal
- Auto-scan
- True diversity system with removable antennas (BNC connection)
- Volume and squelch controls
- LCD for indicating group/channel, antenna A/B, RF receiving level and AF audio level
- Additional LED level display for indicating audio level
- XLR output and 6.3 mm output
- 8 V supply voltage for active antennas or antenna amplifier (e.g. TXS-875B) is available
- Robust metal housing
- Supplied with power supply

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

## Tekniset tiedot:

### General information

	: -
Description	: receiver unit
Carrier frequency range	: 672.000-696.975 MHz
Audio frequency range	: 30-18,000 Hz
Channels	: 1
THD	: < 0.5%
Dynamic range	: 100 dB
RF S/N ratio	: 105 dB
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	: -
Transmitting power	: -
Operating range	: -
Power supply transmitter	: -
Width transmitter	: -
Height transmitter	: -
Depth transmitter	: -
Weight transmitter	: -
Connections transmitter	: -

### Specifications receiver

Audio signal receiver	: 350 mV/600 Ohm (jack) 25 mV/600 Ohm (XLR, bal.)
Power supply receiver	: via encl. plug-in power supply
Width receiver	: 212 mm
Height receiver	: 45 mm
Depth receiver	: 180 mm
Weight receiver	: 930 g
Connections receiver	: 1 x XLR, bal., 1 x 6.3 mm jack, unbal.