

HOMEX-1 - Condenser USB Microphone



USB small diaphragm condenser microphone,
for home recording and presentation.

- For operating directly at a PC or laptop
- No driver installation required, device will be identified automatically
- Integrated high-quality A/D converter: 48 kHz/16 bits
- 1.25 cm (½") diaphragm
- Stepless crossfading control (monitor and PC) with mute button
- Adjustable 3.5 mm stereo headphone output
- Microphone desk stand with 9 mm ((tm)) tripod socket and microphone holder with 16 mm ((tm)) to 9 mm ((tm)) adapter screw
- Supplied with 1.8 m USB connection cable
- Suitable for Windows or Mac

Tekniset tiedot:

| | |
|--------------------------------|------------------------------|
| Description | : small diaphragm microphone |
| Version | : USB |
| Transmission method | : cable |
| Polar pattern | : cardioid |
| System | : electret condenser |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 20-20,000 Hz |
| Nominal impedance | : - |
| Sensitivity | : 16 mV/Pa |
| S/N ratio | : ? 87 dB |
| Max. sound pressure | : 130 dB |
| Power supply | : DC 5 V via USB interface |
| Gooseneck length | : - |
| Housing material | : diecast zinc |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : Å~ 57 mm x 210 mm |
| Weight | : 470 g |
| Cable | : 1.8 m |
| Connection | : USB Type-B jack |
| Packing dimensions (W x H x L) | : 0.202 x 0.255 x 0.108 m |
| Gross weight | : 1.056 kg |
| Net weight | : 0.785 kg |
| Audio Codecs | : - |
| PoE | : - |
| LAN | : - |
| Software, app | : - |
| Sampling rates | : 48 kHz |
| Resolution | : 16 Bit |