

## WALL-06T/WS - PA Speaker Cabinet



### Pairs of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white (WS) or black (SW)
- 4 power taps as well as switchable to 8 Ohm operation
- 16 cm (6") bass-midrange speaker and 25 mm (1") dome tweeter
- Suitable for outdoor applications (IP65)
- Weatherproof
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

## Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white
- 4 power taps as well as switchable to 8 Ohm operation
- 16 cm (6") bass-midrange speaker and 25 mm (1") dome tweeter
- Suitable for outdoor applications (IP65)
- Weatherproof
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

## Tekniset tiedot:

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 100 W
Power rating (RMS)	: 32/16/8/4 W (100 V) 50 W (8 Ohm)
Impedance	: 8 Ohm
Frequency range	: 70-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Full range speaker	: -
Bass speaker	: 16 cm (6") bass-midrange speaker
Midrange speaker	: -
Tweeter	: 25 mm (1") dome tweeter
Number of speakers	: 2
Speaker size	: 6"
Sensitivity	: 90 dB/W/m
Max. rated SPL	: 106 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: IP65
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 196 x 303 x 250 mm (with bracket)
Width	: 196 mm
Height	: 303 mm
Depth	: 250 mm
Weight	: 3.5 kg



Inputs	: spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: for pivoting and tilting
Accessories	: -