


## SPE-150/WS - Loudspeaker



Flush-mount full range speakers, 15 W

- Dual cone
- Slimline design with fixed metal grille

## Tekniset tiedot:

|   |   |
|---|---|
| Impedance (Z)                             | : 4 Ohm   |
| Transmission method                       | : -   |
| Frequency range                           | : 100-12,000 Hz   |
| Resonant frequency (fs)                   | : -   |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : -   |
| Power rating (RMS)                        | : 15 W  |
| Peak music power output (MAX)             | : 30 W  |
| Sensitivity                               | : 89 dB/W/m   |
| Max. rated SPL                            | : -   |
| Max. voltage                              | : -   |
| Radiation angle, horizontal               | : -   |
| Radiation angle, vertical                 | : -   |
| Suspension compl. (Cms)                   | : -   |
| Moving mass (Mms)                         | : -   |
| Mech. Q factor (Qms)                      | : -   |
| Electr. Q factor (Qes)                    | : -   |
| Total Q factor (Qts)                      | : -   |
| Equivalent volume (Vas)                   | : -   |
| DC resistance (Re)                        | : -   |
| Force factor (BxL)                        | : -   |
| Voice coil induct. (Le)                   | : -   |
| Voice coil diameter                       | : -   |
| Voice coil former                         | : -   |
| Linear excursion (X <sub>MAX</sub> )      | : -   |
| Eff. cone area (Sd)                       | : -   |
| Magnet weight                             | : -   |
| Magnet diameter                           | : -   |
| Mounting cutout                           | : $\tilde{\text{A}} \sim 120 \text{ mm}$                      |
| Mounting depth                            | : 34 mm   |
| Mounting hole diameter                    | : -   |
| Hole spacing X-axis                       | : -   |
| Hole spacing Y-axis                       | : -   |
| Dimensions                                | : $\tilde{\text{A}} \sim 153 \text{ mm} \times 45 \text{ mm}$ |
| Outside diameter                          | : $\tilde{\text{A}} \sim 153 \text{ mm}$                      |
| Width                                     | : $\tilde{\text{A}} \sim 153 \text{ mm}$                      |

|                       |           |
|-----------------------|-----------|
| Height                | : -       |
| Depth                 | : 45 mm   |
| Protective class      | : -       |
| Admiss. ambient temp. | : 0-40 °C |
| Weight                | : 500 g   |
| Packing unit          | : 1       |
| Type of speaker       | : 130     |