

NR-254KS - Horn Speaker



Weatherproof horn speaker

- 4 Ohm speaker system
- IP66 tested, protected against powerful water jets
- Especially suitable for voice transmissions
- Robust plastic housing of compact size
- Supplied with zinc-plated mounting bracket and mounting screws

Tekniset tiedot:

| | |
|--------------------------------|---------------------|
| Active/passive | : passive |
| Transmission method | : - |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 25 W |
| Power rating (RMS) | : 12 W |
| Impedance | : 4 Ohm |
| Frequency range | : 800-8,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : - |
| Sensitivity | : 107 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : 90° |
| Radiation angle, vertical | : 90° |
| Features | : - |
| Housing material | : plastic |
| Colour | : black |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : IP66 |
| Admiss. ambient temp. | : -20 °C to +50 °C |
| Power supply | : - |
| Dimensions | : 106 x 106 x 88 mm |
| Width | : 106 mm |
| Height | : 106 mm |
| Depth | : 88 mm |
| Weight | : 1.08 kg |



| | |
|------------------------|----------------|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : weatherproof |
| Accessories | : - |