

PAB-52WP/WS - PA Speaker Cabinet



Weatherproof PA speakers with IP classification.

Exactly the right speakers whenever a high sound quality, a high volume capability and a respective resistance to all weather conditions are required. Ideally suited for permanent open-air applications, e.g. at fairground attractions, PA applications in pedestrian areas, at sports facilities and wherever a weather-protected installation of the speakers is not possible.

Weatherproof high-performance PA speaker system, 50 W

- Compact wideband bass-reflex system in an ABS cabinet
- 100 V or 4 Ohm operation, selectable
- 13 cm (5") high-quality full range speaker with aluminium cone
- Excellent sound characteristics
- Front grille with water-repellent gauze
- Recessed connection terminal with cover plate and high-strength cable gland
- Metal parts and wall bracket made of stainless steel
- Ball-proof according to DIN 18032, Part 3

PROSOUND 05/2011

"The cabinets give a solid impression ... and meet IP45 requirements. All four speaker systems are suitable for pleasant background music ... the large PAB-8WP/WS is capable of quite high volume levels ... however, the small ones should not be underestimated ... these speaker systems are impressive and the price is quite reasonable for weatherproof speaker systems."

Tekniset tiedot:

| | |
|--------------------------------|---------------------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 50/25/12.5 W |
| Impedance | : 4 Ohm |
| Frequency range | : 60-18,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : wideband bass-reflex |
| Full range speaker | : 13 cm (5") full range speaker |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : 13 cm (5") |
| Sensitivity | : 87 dB/W/m |
| Max. rated SPL | : 104 dB |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : ABS |
| Colour | : white |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : yes |
| Protection class | : IP45 |
| Admiss. ambient temp. | : -10 °C to +40 °C |
| Power supply | : - |
| Dimensions | : 200 x 200 x 190 mm |
| Width | : 200 mm |
| Height | : 200 mm |
| Depth | : 190 mm |
| Weight | : 5.1 kg |



| | |
|------------------------|------------------|
| Inputs | : screw terminal |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |