

## HSE-80 - Headworn Microphone



Electret headband microphone

- For vocal and speech applications
- Very comfortable to wear
- Secure fit also during sports applications
- High-quality electret cartridge
- 3-pole mini XLR inline jack for connection to an optional phantom power supply adapter (EMA-1, EMA-300P) or a pocket transmitter TXS-...HSE

## Tekniset tiedot:

|                         |                       |
|-------------------------|-----------------------|
| Description             | : headband microphone |
| Version                 | : -                   |
| Transmission method     | : cable               |
| Polar pattern           | : cardioid            |
| System                  | : electret            |
| Carrier frequency range | : -                   |
| Transmitting power      | : -                   |
| Power supply            | : -                   |
| Operating time          | : -                   |
| Audio frequency range   | : 100-12,000 Hz       |
| Nominal impedance       | : 2.2 kOhm            |
| Sensitivity             | : 8.5 mV/Pa           |
| S/N ratio               | : -                   |
| Max. sound pressure     | : 110 dB              |
| Power supply            | : DC 2-10 V           |
| Gooseneck length        | : -                   |
| Housing material        | : -                   |
| Admiss. ambient temp.   | : 0-40 °C             |
| Dimensions              | : -                   |
| Weight                  | : 40 g                |
| Cable                   | : 1 m                 |
| Connection              | : 3-pole mini XLR     |