

## VMX-440/SW - Mixer



### 4-channel microphone line mixer

Mixing made easy! An easy-to-use operating concept and clearly arranged features. Two stereo line sources and two mono microphone sources can be mixed together without any problems. Each input channel features a tone control. The master output levels can be preadjusted via recessed trimming potentiometers in order to protect them against overload. An optional remote switch can mute the stereo master outputs.

- 2 stereo line inputs
- 2 balanced microphone inputs
- Parallel stereo line input on the front panel
- 3-way equalizer for each microphone input
- Common 2-way tone control for the two line inputs
- Muting via optional momentary push-button/switch
- 2 adjustable stereo master outputs
- Master output level can be preadjusted via trimming potentiometers
- Adjustable headphone output
- Stereo record output
- 482 mm (19") rack installation, 1 RS, with supplied mounting brackets

## Tekniset tiedot:

No. of channels	: 4
No. of inputs	: 5
Mic input	: 1 $\hat{A}$ mV/600 $\hat{A}$ Ohm, 2 x 6.3 mm jack, bal.
Line input	: 100 $\hat{A}$ mV/10 $\hat{A}$ kOhm, 3 x RCA L/R
CD input	: -
Phono input	: -
Tape (play)	: -
Aux input	: -
Insert input	: -
Effect return	: -
Master output	: 1-3 $\hat{A}$ V/100 $\hat{A}$ Ohm, 2 x RCA L/R
Record output	: 1 $\hat{A}$ V/100 $\hat{A}$ Ohm, 1 x RCA L/R
Monitor output	: -
Booth output	: -
Aux output	: -
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: ? 32 Ohm, 2 x 15 mW, 1 x 6.3 $\hat{A}$ mm jack
Gooseneck lamp	: -
<b>WiFi</b>	: -
<b>USB</b>	: -
<b>Bluetooth</b>	: -
Frequency range	: 20-20,000 $\hat{A}$ Hz
THD	: 0.05%
S/N ratio	: ? 60 dB
Crosstalk	: -
Equalizer bass	: $\pm$ 12 $\hat{A}$ dB/30 $\hat{A}$ Hz
Equalizer midrange	: $\pm$ 12 $\hat{A}$ dB/1 $\hat{A}$ kHz (voice only)
Equalizer treble	: $\pm$ 12 $\hat{A}$ dB/12 $\hat{A}$ kHz
equalizer	: -
Talkover	: -
Phantom power	: -
Crossfader	: -

Media player	: -
Amplifier	: -
Power supply	: &acd; 230Â V/50Â Hz/10Â VA
Mains voltage	: &sim; 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 10 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 45 mm
Depth	: 180 mm
Rack spaces, RS	: 1
Weight	: 2.25 kg