

PA-1414MX - 10-Channel PA Pre-Amplifier



10-channel PA preamplifier

- 5 XLR input channels, switchable mic/line
- 4 input channels, switchable XLR mic/RCA line
- 2 XLR master outputs
- 1 record output (master1, master2)
- Input channels with level control and output selector switch (master1, master1+2, master2)
- Each master output with 2-way tone control
- Chime button with priority circuit, remote control possible, 2-tone chime or 4-tone chime, siren (selectable)
- 1 push-to-talk connection, RJ45, with priority circuit (suitable for PA-4000PTT)
- Low cut filter can be activated as required for each microphone input
- Priority circuit for channels 2-3
- Phantom power for electret microphones can be activated as required for each XLR input channel
- Mains operation or 24 V emergency power operation

Tekniset tiedot:

| | |
|--|--|
| Peak output power | : - |
| Power rating | : - |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : - |
| Power rating at 8 Ohm | : - |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm | : - |
| bridged operation | |
| Power rating with 8 Ohm | : - |
| bridged operation | |
| Output impedance | : - |
| Channels | : 10 |
| Zones | : - |
| Inputs | : 2.5 mV, bal. (mic), 250 mV, bal. (line XLR), 250 mV, unbal. (line RCA) |
| Attenuation factor | : - |
| Frequency range | : 20-20,000 Hz (-0.5 dB) |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : ± 10 dB/100 Hz |
| Equalizer midrange | : - |
| Equalizer treble | : ± 10 dB/10 kHz |
| S/N ratio | : ? 60 dB (mic), ? 75 dB (line) |
| Crosstalk attenuation | : - |
| THD | : < 0.05% |
| Mains voltage | : \approx 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 15 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : DC 24 V |
| Power supply (possible alternative) | : DC 0.5 A |
| Admiss. ambient temp. | : 0-40 °C |

Width : 482 mm
Height : 45 mm
Depth : 240 mm





| | |
|-----------------|--|
| Rack spaces, RS | : 1 |
| Weight | : 2.5 kg |
| Connections | : 9 x XLR (mic/line inputs), 4 x RCA L/R (line inputs), 1 x RJ45 (push-to-talk microphone), 2 x XLR (outputs), 1 x RCA L/R (record output) |