

## ATS-10PS - Charger



### 16-channel Mono PLL Audio Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Wireless transmissions of audio signals with one transmitter and one receiver are also possible
- Due to the small frequency spacing in this free frequency range, a simultaneous operation of not more than two transmitters is recommended (with optimum conditions, up to 7 transmitters max. are possible)
- Licence-free in the EU

### Automatic quick-charge station,

for simultaneously charging rech. batteries of two devices from the ATS-10 series.

- Average charging time, depending on capacity and condition of the rechargeable batteries used: approx. 3-4 hours, e.g. for 1,300 mAh rech. batteries
- Operating LEDs for "charging" and "charging completed"
- Including plug-in power supply

## Tekniset tiedot:

|                       |                                  |
|-----------------------|----------------------------------|
| Description           | : quick charging station         |
| Nominal value         | : 2 devices                      |
| Type                  | : automatic                      |
| Colour                | : black                          |
| Material              | : -                              |
| Suitable for          | : ATS-10R, ATS-10TM              |
| Power supply          | : via encl. plug-in power supply |
| Admiss. ambient temp. | : 0-40 °C                        |
| Dimensions            | : 232 x 51 x 140 mm              |
| Length                | : -                              |
| Mounting dimensions   | : -                              |
| Weight                | : 350 g                          |
| Connections           | : -                              |
| Other features        | : -                              |
| Packing unit          | : 1                              |