

## ATS-20R - Receiver



### 16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- High operating range
- Frequency range perfectly adapted to voice transmissions
- Parallel operation of up to 4 different channels possible without any interference
- Extra small and lightweight transmitters and receivers
- Licence-free in the EU

### 16-channel miniature receiver

- Supplied with matching clip-on earphone
- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)
- LCD for indicating channel, carrier signal, volume and battery status
- Autolock function
- Lanyard
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 87 x 12 mm
- Weight: 37 g

**Licence-free in the EU.**

## Tekniset tiedot:

### General information

Description	: -
Carrier frequency range	: 16-channel digital miniature receiver
Audio frequency range	: 863-865 MHz
Channels	: -
THD	: -
Dynamic range	: -
RF S/N ratio	: -
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	: -
Transmitting power	: -
Operating range	: -
Power supply transmitter	: -
Width transmitter	: -
Height transmitter	: -
Depth transmitter	: -
Weight transmitter	: -
Connections transmitter	: -
<b>Specifications receiver</b>	: -
Audio signal receiver	: -
Power supply receiver	: integrated rech. lithium batt. (3.7 V/600 mAh)
Width receiver	: 40 mm
Height receiver	: 87 mm
Depth receiver	: 12 mm
Weight receiver	: 37 g
Connections receiver	: 3.5 mm jack (earphone), micro USB charging port