

---

-

## Tekniset tiedot:

Peak output power	: -
Power rating	: 2 x 25 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 10 W @ DC 12 V 2 x 16 W @ DC 15 V
Power rating at 8 Ohm	: 2 x 6 W @ DC 12 V 2 x 10 W @ DC 15 V 2 x 25 W @ DC 24 V
Power rating at 16 Ohm	: 2 x 3.5 W @ DC 12 V 2 x 5.5 W @ DC 15 V 2 x 15 W @ DC 24 V
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: -
Attenuation factor	: -
Frequency range	: 45-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: -
Crosstalk attenuation	: -
THD	: -
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -

Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 175 mm
Height	: 100 mm
Depth	: 37 mm

---

Rack spaces, RS	: -
Weight	: 176 g
Connections	: RJ45 (LAN) 3.5 mm jack (AUX) screw terminal (speakers, power supply)