

## EDL-224ABC - PA Ceiling Speaker



PA A/B ceiling speaker,  
with EN 54-24 certification. For systems with A/B speaker distribution. Cost-effective reduction of the required ceiling cutouts.

- 100 V line technique
- 2 separate speaker systems
- Full range speaker with a very high efficiency and high maximum volume level
- Metal housing
- Fire protection cover
- Quick mounting facility
- 3 power taps via push terminals
- Ball-proof according to DIN 18032, Part 3

## Tekniset tiedot:

|   |                                 |
|---|---------------------------------|
| Impedance (Z)                             | : -                             |
| Transmission method                       | : 100 V                         |
| Frequency range                           | : 75-20,000 Hz                  |
| Resonant frequency (fs)                   | : -                             |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : -                             |
| Power rating (RMS)                        | : 2 x 6/2 x 3/2 x 1.5 W         |
| Peak music power output (MAX)             | : -                             |
| Sensitivity                               | : 92 dB/W/m                     |
| Max. rated SPL                            | : -                             |
| Max. voltage                              | : -                             |
| Radiation angle, horizontal               | : -                             |
| Radiation angle, vertical                 | : -                             |
| Suspension compl. (Cms)                   | : -                             |
| Moving mass (Mms)                         | : -                             |
| Mech. Q factor (Qms)                      | : -                             |
| Electr. Q factor (Qes)                    | : -                             |
| Total Q factor (Qts)                      | : -                             |
| Equivalent volume (Vas)                   | : -                             |
| DC resistance (Re)                        | : -                             |
| Force factor (BxL)                        | : -                             |
| Voice coil induct. (Le)                   | : -                             |
| Voice coil diameter                       | : -                             |
| Voice coil former                         | : -                             |
| Linear excursion (X <sub>MAX</sub> )      | : -                             |
| Eff. cone area (Sd)                       | : -                             |
| Magnet weight                             | : -                             |
| Magnet diameter                           | : -                             |
| Mounting cutout                           | : $\varnothing$ 230 mm          |
| Mounting depth                            | : 110 mm                        |
| Mounting hole diameter                    | : -                             |
| Hole spacing X-axis                       | : -                             |
| Hole spacing Y-axis                       | : -                             |
| Dimensions                                | : $\varnothing$ 252 mm x 115 mm |
| Outside diameter                          | : $\varnothing$ 252 mm          |
| Width                                     | : $\varnothing$ 252 mm          |



|                       |           |
|-----------------------|-----------|
| Height                | : -       |
| Depth                 | : 115 mm  |
| Protective class      | : -       |
| Admiss. ambient temp. | : 0-40 °C |
| Weight                | : 1.84 kg |
| Packing unit          | : 1       |
| Type of speaker       | : 2 x 100 |