

## ESP-1000AB - PA Wall-/Ceiling Speaker



PA A/B wall speaker,  
with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 2 x 10 cm full range speaker
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Plastic cabinet with open rear panel with protective metal front grille
- Supplied with aluminium mounting bracket, screws and wall plugs

## Tekniset tiedot:

|                                |                    |
|--------------------------------|--------------------|
| Active/passive                 | : passive          |
| Transmission method            | : 100 V            |
| Total output power             | : -                |
| Power rating (RMS)             | : -                |
| Total power rating             | : -                |
| Power rating (RMS)             | : 2 x 6/3/1.5 W    |
| Impedance                      | : -                |
| Frequency range                | : 80-20,000 Hz     |
| THD                            | : -                |
| S/N ratio                      | : -                |
| Input signal                   | : -                |
| System                         | : -                |
| Full range speaker             | : 2 x 10 cm        |
| Bass speaker                   | : -                |
| Midrange speaker               | : -                |
| Tweeter                        | : -                |
| Number of speakers             | : 2                |
| Speaker size                   | : 10 cm            |
| Sensitivity                    | : 92 dB/W/m        |
| Max. rated SPL                 | : 100 dB           |
| Radiation angle, horizontal    | : 160°             |
| Radiation angle, vertical      | : 160°             |
| Features                       | : -                |
| Housing material               | : metal            |
| Colour                         | : white            |
| Mounting device                | : bracket          |
| Protected against ball rebound | : -                |
| Protection class               | : -                |
| Admiss. ambient temp.          | : -10 °C to +50 °C |
| Power supply                   | : -                |
| Dimensions                     | : 220 mm x 100 mm  |
| Width                          | : 220 mm           |
| Height                         | : -                |
| Depth                          | : 100 mm           |
| Weight                         | : 1.98 kg          |



|                        |     |
|------------------------|-----|
| Inputs                 | : - |
| Outputs                | : - |
| Replacement voice coil | : - |
| Other features         | : - |
| Accessories            | : - |