

ECMS-70 - Studio Condenser Microphone



Large diaphragm condenser microphone,
for professional studio applications.

- 2.5 cm (1") extra thin gold-plated diaphragm
- 48 V phantom power
- Supplied with vibration absorbing support (spider) with 16 mm ((tm)) tripod socket and 9 mm ((tm)) adapter screw, microphone windshield and leather bag

delamar.de 03/2018

“Easy-to-use large diaphragm condenser microphone with cardioid polar pattern at an attractive price. The ECMS-70 from IMG STAGELINE provides an excellent sound ... a full-bodied, relaxing sound with subtle treble boost, sufficient detail and almost non-existent background noise. It features a low weight and is of neat workmanship. ... all in all, a top microphone for the intended target group. Who is it for(tm) It is suitable for people who want more when they start with home recording of vocals and co. and for advanced users up to semi-professionals.”

Tekniset tiedot:

| | |
|-------------------------|------------------------------|
| Description | : large diaphragm microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : cardioid |
| System | : condenser |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 20-20,000 Hz |
| Nominal impedance | : 150 Ohm |
| Sensitivity | : 20 mV/Pa |
| S/N ratio | : 78 dB |
| Max. sound pressure | : 132 dB |
| Power supply | : DC 48 V, phantom power |
| Gooseneck length | : - |
| Housing material | : metal |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : Å~ 50 mm x 185 mm |
| Weight | : 310 g |
| Cable | : - |
| Connection | : XLR, bal. |