


MPT-025 - Piezo Tweeter



Piezo tweeter

- Large rectangular design
- Deep low limit frequency

Tekniset tiedot:

Impedance (Z)	: ? 1,000 Ohm
Transmission method	: -
Frequency range	: 3,000-20,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: -
Peak music power output (MAX)	: 115 W (8 Ohm system) 225 W (4 Ohm system)
Sensitivity	: 92 dB/W/m
Max. rated SPL	: -
Max. voltage	: ~ 30 V
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: 155 x 55 mm
Mounting depth	: 100 mm
Mounting hole diameter	: 63.5 mm
Hole spacing X-axis	: 170 mm
Hole spacing Y-axis	: -
Dimensions	: 187 x 80 x 106 mm
Outside diameter	: -
Width	: 187 mm



Height	: 80 mm
Depth	: 106 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.094 kg
Packing unit	: 1
Type of speaker	: -