

PA-2400RC - PA Desk Microphone



PA zone paging desktop microphone,
for connection to PA-2410Z and PA-2420Z.

- Selection buttons for speaker zones 1-20
- Start/stop function for 6 selectable announcements which are stored in the digital module PA-1120DMT, available at option
- LED indication for various functions
- Automatic chime via microphone announcement button
- Adjustable microphone sensitivity
- 24 V power supply via PA-2410Z, PA-2420Z
- RJ45 jacks for connection to additional PA-2400RC with slave/priority switch
- Up to 3 x PA-2400RC can be connected to PA-2410Z or PA-2420Z
- Supplied with 3 m connection cable (Cat. 5e)

Tekniset tiedot:

| | |
|-------------------------|---------------------------------------|
| Description | : PA desktop microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : - |
| System | : - |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : via PA-2410Z, PA-2420Z |
| Operating time | : - |
| Audio frequency range | : - |
| Nominal impedance | : - |
| Sensitivity | : - |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 275 x 51 x 156 mm (console housing) |
| Weight | : 1.4 kg |
| Cable | : - |
| Connection | : RJ45 (input/link) |