

SPEECH-204 - Amplifier System

new



Professional lectern with integrated 2-channel multifrequency receiver unit with UHF PLL technology

- Built-in high-performance mixing amplifier and speaker system, 75 W
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz)
- Integrated limiter
- 3 inputs via comb. jack mic (XLR)/line (6.3 mm jack) with 3-way equalizer and gain control
- 1 stereo line input via RCA jacks with gain control
- 2 shock-absorbing XLR jacks on the top part of the lectern for 2 optional gooseneck microphones (use one microphone input each), with phantom power
- 1 stereo line output via RCA jacks
- 2-way speaker system
- Integrated light in the top part of the lectern
- Column with 2 document compartments and 2 storage compartments
- 2 castors

Supplied w/o gooseneck microphone. Matching microphone EMG-650P is available at option.

Matching microphone transmitters or pocket transmitters are available at option, e.g. TXA-800HSE or TXA-800HT.

Licence-free in the EU.

Tekniset tiedot:

Rated power (P_{RMS})	: 75 W
Peak output power	: 100 W
Frequency range	: 60-20,000 Hz
Carrier frequency	: 863.1-864.9 MHz
Operating range	: ? 25 m
Inputs	: 15Â mV (mic 1), 5Â mV (mic 2-3), 220Â mV (line 1-3), 250Â mV (line)
Link	: -
THD	: -
Max. SPL	: -
Equalizer, bass	: ± 12 dB/60 Hz
Equalizer, midrange	: ± 7 dB/1 kHz
Equalizer, treble	: ± 12 dB/15 kHz
Power supply	: ∿ 230Â V/50Â Hz/180Â VA
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 540 x 1140 x 430Â mm
Weight	: 33 kg
Connections	: 3 x XLR (mic), 3 x 6.3 mm jack (line), 1 x RCA L/R (line in), 1 x RCA L/R (line out)