

ETS-230/WS - PA Speaker Column



Particularly Slim Design

PA column speakers,

in extruded aluminium cabinets, with top and bottom plates of aluminium.

- 100 V line technique
- 5-step power selector switch
- 2 x M6 threaded bushing
- Metal front grille
- Supplied with mounting brackets
- Connection via cable, 2 cores

Tekniset tiedot:

| | |
|--------------------------------|-------------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 30/15/7.5/3.75 W |
| Impedance | : - |
| Frequency range | : 200-15,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 8 |
| Speaker size | : - |
| Sensitivity | : 95 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : aluminium |
| Colour | : white |
| Mounting device | : mounting brackets, M6 |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 105 x 687 x 85 mm |
| Width | : 105 mm |
| Height | : 687 mm |
| Depth | : 85 mm |
| Weight | : 3.9 kg |



| | |
|------------------------|-----|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |